

SPECIFICATION SHEET

VERSION 2,00 **VERSION DATE** 17/05/23 **PRINT DATE** 23/07/24

PRODUCT BLACKWOOD

APPLICATIONS Industrial raw material not intended for direct use.

CLASSIFICATION

REACH REGISTRATION NO. All the ingredients of the mixture have been registered or they are exempt from registration.

SPECIFICATIONS

ASPECT AT 20°C CLEAR MOBILE LIQUID
COLOUR PALE YELLOW
ODOUR WOODY

TENACITY LASTS 2 WEEKS ON A SMELLING STRIP
USAGE A BLEND OF AROMATIC, WOODY AND MUSKY CAPTIVES MAKE UP THIS BASE THAT IS BOTH FRESH AND WARM. ADDS CHARACTER, VOLUME AND TENACITY TO ANY FRAGRANCE.

STABILITY

DENSITY AT 20°C (g / ml) 0,936 - 0,946
DENSITY 25/25 -
REFRACTIVE INDEX nD20 1,4697 - 1,4757
REFRACTIVE INDEX nD25 -
OPTICAL ROTATION (°) /
BOILING POINT (°C) -
MELTING POINT (°C) -
FLASH POINT (°C) 101,00
ASSAY (% GC) -
ACID VALUE (mg KOH/g) -
SOLUBILITY INSOLUBLE IN WATER
VAPOUR PRESSURE NOT DETERMINED
OTHER SOLUBILITIES SOLUBLE IN ETHANOL

OTHER TECHNICAL DATA

STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.