

SPECIFICATION SHEET

VERSION	1,00	VERSION DATE	19/09/22	PRINT DATE	03/05/24
PRODUCT	PALISANDROL FIRMENICH 17979				
APPLICATIONS	Industrial raw material not intended for direct use.				
CLASSIFICATION	WOODY				
REACH REGISTRATION NO.	All the ingredients of the mixture have been registered or they are exempt from registration.				

SPECIFICATIONS

ASPECT AT 20°C	CLEAR MOBILE LIQUID		
COLOUR	COLORLESS TO PALE YELLOW		
ODOUR	A VERY INTENSE AND RICH WOODY SPECIALITY WITH ASPECTS OF DRIED WOOD.		
TENACITY	LASTS MORE THAN 1 WEEK ON A SMELLING STRIP.		
USAGE	LEVELS FROM 0,5% TO 5% CAN BE USED TO UNDERLINE THE WOODY SIDE OF ANY COMPOUND. IT WORKS PARTICULARLY WELL IN COMBINATION WITH SANDALWOOD AND AMBROX DL.		
STABILITY	STABLE IN A WIDE RANGE OF PRODUCTS INCLUDING CREAM, TALCUM POWDER, ANTIPERSPIRANT, SHAMPOO AND SOAP.		
DENSITY AT 20°C (g / ml)	1,028	-	1,038
DENSITY 25/25		-	
REFRACTIVE INDEX nD20	1,4920	-	1,4980
REFRACTIVE INDEX nD25		-	
OPTICAL ROTATION (°)		/	
BOILING POINT (°C)	-		
MELTING POINT (°C)	-		
FLASH POINT (°C)	101,00		
ASSAY (% GC)			
ACID VALUE (mg KOH/g)	-		
SOLUBILITY	SOLUBILITY IN WATER: NOT DETERMINED		
VAPOUR PRESSURE	NOT DETERMINED		
OTHER SOLUBILITIES	SOLUBLE IN ETHANOL		

OTHER TECHNICAL DATA

STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.