

SPECIFICATION SHEET

VERSION 2,00 **VERSION DATE** 20/04/23 **PRINT DATE** 16/08/24

PRODUCT SANDALWOOD OIL CO2
APPLICATIONS Industrial raw material not intended for direct use.
IUPAC NAME SANDALWOOD OIL
PLANT OF ORIGIN Santalum album L.
PART OF THE PLANT WOOD FROM TRUNK AND ROOTS
SYNONYMS

CAS 84787-70-2
CAS 2 8006-87-9
EINECS 284-111-1

FEMA 3005
TARIFF NUMBER 3301294900

REACH REGISTRATION NO. On request. REACH and non-REACH material available for this product.

SPECIFICATIONS

ASPECT AT 20°C CLEAR VISCOUS LIQUID
COLOUR PALE YELLOW TO ORANGE
ODOUR STRONG, WARM, WOODY
TASTE

DENSITY AT 20°C (g / ml) 0,950 - 0,999
DENSITY 25/25 -
REFRACTIVE INDEX nD20 1,4850 - 1,5200
REFRACTIVE INDEX nD25 -
OPTICAL ROTATION (°) -35,00 / -13,00
BOILING POINT (°C) -
MELTING POINT (°C) -
FLASH POINT (°C) 110,00
ASSAY (% GC) -
ACID VALUE (mg KOH/g) -
SOLUBILITY INSOLUBLE IN WATER
VAPOUR PRESSURE NOT DETERMINED
OTHER SOLUBILITIES SOLUBLE 1:3 IN ETHANOL 80%

OTHER TECHNICAL DATA

STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.

THIS PRODUCT HAS NOT BEEN FILTERED DUE TO TECHNICAL REASONS. WE RECOMMEND NOT TO USE IT UNLESS FILTERED WHEN USED AS A RAW MATERIAL IN FOOD INTENDED FOR FINAL CONSUMERS.