

## **SPECIFICATION SHEET**

**VERSION** 2,00 **VERSION DATE** 13/03/20 **PRINT DATE** 20/05/24

PRODUCT VETIMOSS

APPLICATIONS Industrial raw material not intended for direct use.

IUPAC NAME 2-TERT-BUTYL-1,4-DIMETHOXYBENZENE

SYNONYMS VETIMOSS, VETYLBOIS, VETTI ETHER, VETTY ETHER

 FORMULA
 C12 H18 O2

 MOLECULAR WEIGHT
 194,00

 CAS
 21112-37-8

**EINECS** 244-216-5

**TARIFF NUMBER** 2909309090

**REACH REGISTRATION NO.** Exempt from registration (imported/manufactured < 1 ton/year)

**SPECIFICATIONS** 

ASPECT AT 20°C CLEAR MOBILE LIQUID COLOUR COLORLESS TO YELLOW

**ODOUR** OUTDOOR, FOREST, DAMP WOOD, POTATO

**TASTE** 

**DENSITY AT 20°C (g / ml)** 0,994 - 0,996

DENSITY 25/25

**REFRACTIVE INDEX nD20** 1,5090 - 1,5120

REFRACTIVE INDEX nD25
OPTICAL ROTATION (°)
/

BOILING POINT (°C) 
MELTING POINT (°C) 
FLASH POINT (°C) 93,30

ASSAY (% GC) > 98

ACID VALUE (mg KOH/g) -

SOLUBILITYINSOLUBLE IN WATERVAPOUR PRESSURE0,01 kPa (0,1 mmHg) (20°C)OTHER SOLUBILITIESSOLUBLE IN ETHANOL

OTHER TECHNICAL DATA
SUBSTANTIVITY: 72 HOURS ON A SMELLING STRIP.

## STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE.

PURGE HEADSPACE WITH NITROGEN.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.