

SPECIFICATION SHEET


VERSION 2,00 **VERSION DATE** 13/03/20 **PRINT DATE** 30/12/24

PRODUCT VETIMOSS
APPLICATIONS Industrial raw material not intended for direct use.
IUPAC NAME 2-TERT-BUTYL-1,4-DIMETHOXYBENZENE
SYNONYMS VETIMOSS, VETYLBOIS, VETTI ETHER, VETTY ETHER

FORMULA C12 H18 O2
MOLECULAR WEIGHT 194,00
CAS 21112-37-8

EINECS 244-216-5

TARIFF NUMBER 2909309090



REACH REGISTRATION NO. Exempt from registration (imported/manufactured < 1 ton/year)

SPECIFICATIONS

ASPECT AT 20°C	CLEAR MOBILE LIQUID
COLOUR	COLORLESS TO YELLOW
ODOUR	OUTDOOR, FOREST, DAMP WOOD, POTATO
TASTE	
DENSITY AT 20°C (g / ml)	0,994 - 0,996
DENSITY 25/25	-
REFRACTIVE INDEX nD20	1,5090 - 1,5120
REFRACTIVE INDEX nD25	-
OPTICAL ROTATION (°)	/
BOILING POINT (°C)	-
MELTING POINT (°C)	-
FLASH POINT (°C)	93,30
ASSAY (% GC)	> 98
ACID VALUE (mg KOH/g)	-
SOLUBILITY	INSOLUBLE IN WATER
VAPOUR PRESSURE	0,01 kPa (0,1 mmHg) (20°C)
OTHER SOLUBILITIES	SOLUBLE IN ETHANOL

OTHER TECHNICAL DATA SUBSTANTIVITY: 72 HOURS ON A SMELLING STRIP.

STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE.
 PURGE HEADSPACE WITH NITROGEN.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.