

## **SPECIFICATION SHEET**

| VERSION 3,00 VERSIO                               | <b>N DATE</b> 11/03/22   | <b>PRINT DATE</b> 19/05/24                  |
|---|--|---|
| PRODUCT<br>APPLICATIONS<br>IUPAC NAME<br>SYNONYMS | AMBERMOR KETAL IPM<br>Industrial raw material not intended for direc<br>3,8,8,11a-TETRAMETHYLDODECAHYDR<br>AMBER OXEPIN, AMBERKETAL, Z11, KE | O-5H-3,5a-EPOXY-NAPHT[2,1-C]OXEPIN (IN SOLV |
| FORMULA<br>MOLECULAR WEIGHT                       | C18 H30 O2<br>278,00   | $\sim$                                      |
| CAS   | 57345-19-4   |   |
| EINECS  | 260-686-4  |   |
| TARIFF NUMBER                                     | 3302909000   |   |
| KOSHER CERTIFICATE                                | AVAILABLE ON REQUEST   | ∕\́Ĥ ́                                      |
| <b>REACH REGISTRATION NO.</b>                     | Exempt from registration (imported/manufac   | ctured < 1 ton/year)                        |

## **SPECIFICATIONS**

ASPECT AT 20°C COLOUR ODOUR TASTE DENSITY AT 20°C (g / ml) DENSITY 25/25 **REFRACTIVE INDEX nD20 REFRACTIVE INDEX nD25 OPTICAL ROTATION (°) BOILING POINT (°C)** MELTING POINT (°C) FLASH POINT (°C) ASSAY (% GC) ACID VALUE (mg KOH/g) SOLUBILITY VAPOUR PRESSURE **OTHER SOLUBILITIES** 

COLORLESS AMBER, WOODY, MUSKY 0,860 - 0,875 -1,4360 - 1,4460 1,4340 - 1,4440 / ---100,00 MAIN PEAK 8,5% APPROX. (SINGLE PEAK) -INSOLUBLE IN WATER 0,0008946 mm Hg at 23°C SOLUBLE IN ETHANOL

CLEAR MOBILE LIQUID/SOLID

**OTHER TECHNICAL DATA** 

## **STABILITY AND STORAGE**

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE. PURGE HEADSPACE WITH NITROGEN. IT CONTAINS 91,5% OF ISOPROPYL MYRISTATE.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.