

SPECIFICATION SHEET

VERSION 2,00 VERSIO	N DATE 13/03/20	PRINT DATE	18/05/24
PRODUCT APPLICATIONS IUPAC NAME SYNONYMS	VETIMOSS Industrial raw material not intended for direct use. 2-TERT-BUTYL-1,4-DIMETHOXYBENZENE VETIMOSS, VETYLBOIS, VETTI ETHER, VETTY	Y ETHER	
FORMULA MOLECULAR WEIGHT CAS	C12 H18 O2 194,00 21112-37-8		
EINECS	244-216-5	Ų	
TARIFF NUMBER	2909309090		
REACH REGISTRATION NO.	Exempt from registration (imported/manufactured < 1 ton/year)		

SPECIFICATIONS

ASPECT AT 20°C	CLEAR MOBILE LIQUID	
COLOUR	COLORLESS TO YELLOW	
ODOUR	OUTDOOR, FOREST, DAMP WOOD, POTATO	
TASTE		
DENSITY AT 20°C (g / ml)	0,994	- 0,996
DENSITY 25/25		-
REFRACTIVE INDEX nD20	1,5090	- 1,5120
REFRACTIVE INDEX nD25		-
OPTICAL ROTATION (°)		/
BOILING POINT (°C)	-	
MELTING POINT (°C)	-	
FLASH POINT (°C)	93,30	
ASSAY (% GC)	> 98	
ACID VALUE (mg KOH/g)	-	
SOLUBILITY	INSOLUBLE IN WATER	
VAPOUR PRESSURE	0,01 kPa (0,1 mmHg) (20ºC)	
OTHER SOLUBILITIES	SOLUBLE IN ETHANOL	

OTHER TECHNICAL DATA

SUBSTANTIVITY: 72 HOURS ON A SMELLING STRIP.

STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE. PURGE HEADSPACE WITH NITROGEN.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.